

APPLICATION
FOR
UNITED STATES LETTERS PATENT

TITLE: PARTITIONING FOR MODEL-BASED DESIGN
APPLICANT: HOWARD TAITEL

CERTIFICATE OF MAILING BY EXPRESS MAIL

Express Mail Label No. EL224699551US

I hereby certify under 37 CFR §1.10 that this correspondence is being deposited with the United States Postal Service as Express Mail Post Office to Addressee with sufficient postage on the date indicated below and is addressed to the Commissioner for Patents, Washington, D.C. 20231.

Date of Deposit July 20, 2001

Signature

Typed or Printed Name of Person Signing Certificate

04899-058001-020220

TECHNICAL FIELD

This invention relates to partitioning objects for model-based design.

BACKGROUND

5 An object model is a formal description of an object-oriented application. Semantic elements of an object model describe object classes, attributes of object classes, relationships between object classes and inheritance between object classes. One example object-oriented application is block diagram modeling.

10 Dynamic real-world systems such as electrical circuits, shock absorbers, braking systems, and many other electrical, mechanical and thermodynamic systems may be modeled, simulated and analyzed on a computer system using block diagram modeling. Block diagram modeling graphically depicts time-dependent mathematical

15 relationships among a system's inputs, states and outputs, typically for display on a graphical user interface (GUI). Block diagram modeling may also be used to simulate the behavior of a system for a specified time span.

Block diagram modeling can also be used to design algorithms

20 to control the real-world systems being modeled, i.e., a block diagram can be converted to a standalone real-time program and executed on a target system. A modeling diagram can interface

with the generated real-time program to exchange run-time data, e.g., change parameters or upload data.

Real-time systems may be thought of as having two main components. A first component is a real-time program required to run a hardware device, such as control logic. A second component is interface code for runtime analysis, visualization and control of the real-time program.

SUMMARY

In general, according to one aspect of the invention, a method includes identifying portions of a model as being either critical to a real-time execution of the model or non-critical to a real-time execution of the model, and generating code that is capable of real-time execution based on the critical portions of the model.

One or more of the following features may also be included. The non-critical portions are post-processing units. Post-processing units are logical units of the model that have no data outputs that feed non-post-processing sections of the model. Generating further includes establishing an inter-process communication link between the code and the non-critical portions of the model. The method may further include receiving output from the code via the inter-process communications link. The method may also include executing the code on a target processor.

The method may also include processing the output in the non-critical portions of the model.

In general, according to another aspect of the invention, a method includes specifying a model, the model including sections, a first subset of the sections designated post-processing unit sections and a second subset of the sections designated as core processing unit sections, and generating software source code for the model with a code generator using the second subset.

One or more of the following features may also be included.

The post-processing unit sections are logical units of the model that have no data outputs that feed core processing unit sections. The method may further include linking the code to the first subset of sections through an inter-process communication link, and executing the code on a target processor. Specifying the model includes receiving a user input through a graphical user interface (GUI). Generating includes applying a set of software instructions resident in the code generator to the second subset. The method may further include receiving output from the code via the inter-process communication link and processing the output in the first subset.

In general, in another aspect of the invention, a system includes a graphical user interface (GUI) adapted to receive user inputs to specify components of a model, the components containing a first subset of sections designated as post-processing elements

of a model and a second subset of sections designated as core elements of the model.

One or more of the following features may also be included. The system may further include an automatic code generator to
5 generate code capable of real-time execution based on the second subset of the sections. The second subset includes elements representing essential computational components of the model. The system may further include a link to provide inter-process communication between the code and the first subset of sections of
10 the model. The first subset is non-real time post-processing sections. The automatic code generator includes a set of pre-defined instructions resident in the automatic code generator to generate code corresponding to the second subset. The code is C programming language. The system may further include a compiler
15 for compiling the code for a target processor.

In general, in another aspect the invention features a method including receiving user input through a graphical user interface (GUI) specifying a block diagram model, the block diagram model including sections, a first subset of the sections designated
20 post-processing unit sections and a second subset of the section designated as core processing unit sections, generating software source code for the block diagram model with a code generator using the second subset, linking the software source code to the

first subset via an inter-process communication link, and compiling the software source code into executable code.

One or more of the following features may also be included. The method may further include executing the executable code on a target processor.

Embodiments of the invention may have one or more of the following advantages.

Partitioning a model diagram achieves a division of processing load between a target process and a host process.

Partitioning based on user-defined properties ensures that no target code is generated for sections of a model diagram that perform run-time post-processing operations. Arbitrary portions of a model diagram can be specified for host-based, post-processing of target signals.

Run-time post processing of target data can be seamlessly specified in a model diagram environment. Sections of the model diagram that perform real-time post-processing are marked as such by a user and subsequently excluded from the real-time program during code generation. Run-time post-processing operations include logging, analysis, data transformations, visualization and non-hard-real-time feedback control of the target system.

A user can specify an arbitrary portion of the model diagram as a post-processing unit (PPU).

User-defined blocks can be specified in a textual language and included in the PPU, allowing coding the post process operation as a mixture of graphical and textual programming. Automatic partitioning of PPUs allows for the seamless transition, with respect to analysis, visualization and run-time target control, between the various stages of a design cycle. The same model diagram is used at all stages of the design cycle, from simulation and rapid prototyping to embedded code. Sections of the model diagram that are stripped from the generated code are completely functional. The fact that the core computations are running in the target and that the host is running the PPUs is transparent to the end user. This enables efficient, production style code to be generated without the loss of run-time analysis, visualization and autonomous tuning of the target.

The ability to run entire sections of the model diagram as host-based PPUs allows the post-processing operations to be programmed all, or in part, in the model diagram language as opposed to textual languages such as the C programming language.

A data object enables a user to fully define the information related to the data to be used with a model-based block diagram.

Other features and advantages of the invention will become apparent from the following description, including the claims and drawings.

DESCRIPTION OF DRAWINGS

FIG. 1 shows a system.

FIG. 2 shows a block diagram model.

FIG. 3 shows a code generation process.

5 FIG. 4 shows an example of the automatic code generation process.

Like reference symbols in the various drawings indicate like elements.

DETAILED DESCRIPTION

10 FIG. 1 shows a system 10. The system 10 includes a host computer 12, such as a personal computer (PC). Computer 12 may be connected to a network 14, such as the Internet, that runs TCP/IP (Transmission Control Protocol/Internet Protocol) or another protocol. Connections may be via Ethernet, wireless link, or
15 telephone line.

Host computer 12 contains a processor 16 and a memory 18. Memory 18 stores an operating system ("OS") 20 such as Windows98® or Linux, a TCP/IP protocol stack 22 for communicating over network 14, and machine-executable instructions 24 executed by
20 processor 16 to perform a code generation process 42 below. Host computer 12 also includes an input/output (I/O) device 26 for display of a graphical user interface (GUI) 28 to a user 30.

The host computer 12 communicates with a target computer 32 via a communications link 34. The target computer 32 runs a real-time operating system (RTOS) 36. The target computer 32 also includes an input/output (I/O) port 38 for producing hardware I/O to a hardware device 40 connected to the target computer 32.

The code generation process 42 executes in the host computer 12. The code generation process 42 is a process in which a behavior represented by a modeling diagram executing in computer 12 and being displayed on the GUI 28 is translated into a standalone, real-time software program code, e.g., C code. An example automatic code generator is the Target Language Compiler included in the Real-Time Workshop Code generation process from MathWorks, Inc. of Natick, Massachusetts, incorporated herein by reference. The real-time code includes only code executing in the target computer 32 that is characterized as critical for control of the hardware device 40 and not code generated for other devices (not shown) that perform off-line operations such as run-time analysis and visualization of control signals; this code would be characterized as non-critical.

Referring to FIG. 2, a block diagram model 50 is a pictorial model of a dynamic system. The block diagram 50 is specified by the user 30 and displayed on the GUI 28. The block diagram model 50 includes of a set of symbols, called blocks 52, interconnected by lines 54. Each of the blocks 52 represents an elementary

dynamic system that produces an output either continuously (a continuous block) or at specific points in time (a discrete block). The lines 54 represent connections of block inputs to block outputs.

5 Every block in the block diagram model 50 is an instance of a specific type of block. The type of block determines the relationship between a block's outputs and its inputs, states, and time. The block diagram model 50 may contain any number of instances of any type of block needed to model a system. The

10 blocks 52 are also characterized as critical real-time components of the block diagram model 50. The block diagram model 50 also includes two analysis/visualization components, i.e., a strip chart 54 and a gauge 56; these components are characterized as non-critical. As is typical in the block diagram model 50, real-

15 time components and analysis/visualization components are intermingled. As will be described below, code generated for the block diagram model 50 and executing on the target computer 32 only includes the critical real-time components, called the core elements, that are crucial to the control of the hardware device

20 40. No code is generated for devices such as the strip chart 54 and gauge 56 that perform off-line operations such as run-time analysis and visualization of control signals. The process 42 determines which components of the block diagram 50 are core

elements and which components are non-essential elements, as is described below.

Certain definitions are useful in the description herein.

Core or critical elements are computational elements of a block diagram, e.g., blocks and signals, that represent essential computations of a real world system. By essential we mean those elements that are critical to the control of the hardware device 40. For example, controller logic is a core real-time element.

Post processing refers to performing operations on data generated by the target computer 32 and acquired by the host computer 12. For example, signal data retrieved from the target computer 32 may undergo a coordinate transformation and smoothing procedure for the purpose of visual display on the GUI 28. This coordinate transformation and smoothing is not included in code executing in the target computer 32 since it is not a core operation.

Run time refers to the fact that the post processing occurs in parallel with the core processing that is occurring on the target computer 32. Data generated by the target computer 32 is acquired via the communication link 34, allowing interactive analysis of data as well as host-based, autonomous control of the target computer program. Run time also refers to simulating the block diagram model 50 in interpreted mode on the host computer

12., i.e., PPUs are also functional during interpretive host-based simulations.

Post processing unit (PPU) refers to a logical section, or unit, of the block diagram model 50 used for run-time post processing of data. Example run-time post processing operations include logging, analysis, data transformation, visualization and non-hard-real-time feedback control of the target process. Run-time post processing is performed by the host computer 12 and not by the target computer 32, thus reducing the computational load of the target computer 32.

The block diagram model 50 includes core elements 60 and two PPUs, i.e., PPU 62 and PPU 64. The block diagram model 50 is simulated by running all the components, core elements 60, PPU 62 and PPU 64, in an interpreted manner on the host computer 12. When a standalone, run-time program is generated for the block diagram model 50, the PPU 62 and PPU 64 are filtered or excluded from the generated software code. Specifically, no software code will execute on the target computer 32 that is non-essential or non-critical. That is, there is no software code generated for the target computer 32 to perform scaling and data smoothing operations, i.e., PPU 62, as well as the monitoring of the 'P' signal and subsequent target feedback, i.e., PPU 64. The operations performed by PPU 62 and PPU 64 are not required for the target computer 32, only for debugging or monitoring the

performance of the target computer 32. Using inter-process communication over a communication line 66, PPU 64 acquires data from the core elements 60 of the target computer 32 and run-time post processing in the PPU 64 is performed on the host computer 12. Feedback control performed by PPU 64 is realized by sending parameters or commands to the target computer 32 over the communication line 66. The communication line 66 includes a physical link such as TCP/IP, serial or shared memory, and contains messages having formats that indicate the type of message received.

To interface with the core elements 60, the host computer 12 interfaces with the real-time software code executing on the target computer 32, uploads data at the boundary of the PPU 64 and runs the PPU 64. The host block diagram environment does an inverse partitioning of the block diagram model in the process of interfacing to the executing code on the target computer 32. Instead of partitioning away the PPUs 62 and 64, as for software code generation, the PPUs 62 and 64 are initialized to receive and process the raw data from the target computer 32 while the core elements 60 are removed from the execution space. The portion of the block diagram model 50 representing the core elements 60 does not perform any signal calculations on the host computer 12 when in target interface mode.

A slightly more refined definition of a PPU is that it is a logical unit of a block diagram model, or a logical chain of units, that perform run-time processing of target computer signals. The essential characteristic of a PPU is that it has no data outputs that feed non-PPU sections of the block diagram model 50, i.e., a PPU may only perform post processing of target computer signals.

Referring to FIG. 3, the code generation process 42 includes specifying 80 a model of a dynamic system to be simulated and displayed on a graphical user interface. The model graphically depicts the time-dependent mathematical relationships among the system's inputs, states and outputs. A model-based design environment is an executable specification that can be translated to target ready code, deployable on hardware or software platforms. Platforms include CPUs, real-time operating systems, custom ASICs, and hardware FPGAs. The model includes a set of symbols, called blocks, interconnected by signal lines that carry signals. Blocks are functional entities that operate on signal values contained in the signal lines. Each block can have zero or more input signal lines and zero or more output signal lines. Blocks can have states. A state is a variable that determines a block's output and whose current value is a function of the previous values of the block's states and/or inputs.

Once the block diagram model is specified 80, the process 50 executes an automatic code generation process 82. The automatic code generation process determines 84 whether a section of the block diagram model is a post processing unit (PPU). As described above, a PPU is a logical unit of the block diagram model that has no data outputs that feed non-PPU sections of the block diagram model. If the section is marked as a PPU no code is generated 84. If the section is not marked as a PPU, code is generated 86. A communications link is established 88 between the generated code compiled and executed on the target computer and the PPU sections on the host computer.

Referring to FIG. 4, an example of the code generator process 42 can be described in conjunction with Real Time Workshop. Real Time Workshop is a set of tools that generate code from Simulink models for targeting real-time systems. When generating code from a Simulink model 100 using Real-Time workshop 102, a Simulink file 104, e.g., Sample.rtw, is utilized. Real Time Workshop file 106 includes all of the model-specific information required for generating code from the Simulink file 104. The Real Time Workshop file 106 is passed to the target language compiler 108, which uses the Real-Time Workshop file 106 in combination with a set of included system target files and block target files 110 to generate code 112. System target files are used to specify the

overall structure of the generated code 112. Block target files are used to implement the functionality of Simulink blocks.

Sections of the Real-Time Workshop file 106 corresponding to PPU's are internally marked as such. The target language compiler
5 108 ignores these sections and only produces code 112 that includes core elements of the original block diagram model.

Process 42 is not limited to use with the hardware/software configuration of FIG. 1; it may find applicability in any computing or processing environment. Process 42 may be
10 implemented in hardware (e.g., an ASIC {Application-Specific Integrated Circuit} and/or an FPGA {Field Programmable Gate Array}), software, or a combination of hardware and software.

Process 42 may be implemented using one or more computer programs executing on programmable computers that each includes a
15 processor, a storage medium readable by the processor (including volatile and non-volatile memory and/or storage elements), at least one input device, and one or more output devices.

Each such program may be implemented in a high level procedural or object-oriented programming language to communicate
20 with a computer system. Also, the programs can be implemented in assembly or machine language. The language may be a compiled or an interpreted language.

Each computer program may be stored on a storage medium or device (e.g., CD-ROM, hard disk, or magnetic diskette) that is

readable by a general or special purpose programmable computer for configuring and operating the computer when the storage medium or device is read by the computer to perform process 42.

Process 42 may also be implemented as a computer-readable
5 storage medium, configured with a computer program, where, upon
execution, instructions in the computer program cause the computer
to operate in accordance with process 42.

Other embodiments are within the scope of the following claims.